



## **SAFETY DATA SHEET (SDS)**

---

### **1. IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING**

---

#### 1.1. Product Identifier

Substance identification:

Name: R134a  
CAS Number: 00811-97-2  
EC Number: 212-377-0  
REACH Number: 01-2119459374-33-0010

#### 1.2. Relevant identified uses of the substance/mixture and uses advised against

Recommended use:

Refrigerant gas  
Industrial and professional  
Expanding  
Aerosol propellant

#### 1.3. Details of the supplier of the safety data sheet

Company:

TAZZETTI S.P.A  
CORSO EUROPA 600/A  
10088 VOLPIANO (TO) - ITALY-  
Tel. +39 02 66101029 (24 h / 24 h)  
rsg.inquiry@tazzetti.com

#### 1.4. Emergency telephone number

Ph +34 918 878 100

### **2. HAZARDS IDENTIFICATION**

---

#### 2.1. Classification of the substance or mixture

EC regulation criteria 1272/2008 (CLP):  
Warning, Liquef. Gas, Contains gas under pressure

#### 2.2. Label elements

Symbols:



Signal word: Warning

Hazard statements:

H280 Contains gas under pressure; may explode if heated.

Precautionary statements:

P403 Store in a well ventilated place

P410 Protect from sunlight

P273 Avoid release to the environment.

P314 Get medical advice/attention if you feel unwell

Special Provisions:

Contains fluorinated greenhouse gases covered by the Kyoto protocol.



## 2.3. Other hazards

vPvB Substances: None - PBT Substances: None

Contact with liquid may cause cold burns/frostbite.

In high concentrations may cause asphyxiation.

Vapour heavier than air, may accumulate below ground level and cause choking.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

---

### 3.1. Substances

Substance identification:

Name: R134a

Chemical name: 1,1,1,2-Tetrafluoroethane

3.2. Mixtures Not applicable

## 4. FIRST AID MEASURES

---

### 4.1. Description of first aid measures

Skin contact:

In case of frostbite spray with water for at least 15 minutes. Apply a sterile dressing. Obtain medical assistance.

Eye contact:

In case of contact with eyes, rinse immediately (for at least 15 minutes) with plenty of water and seek medical advice.

Ingestion:

Do not induce vomiting. Obtain medical assistance.

Inhalation:

Remove victim to uncontaminated area wearing self contained breathing apparatus. Keep victim warm and rested. Call a doctor. Apply artificial respiration if breathing stopped.

### 4.2. Most important symptoms and effects, both acute and delayed

Misuse or intentional inhalation abuse may cause death without warning symptoms, due to cardiac effects., Other symptoms potentially related to misuse or inhalation abuse are:, Anaesthetic effects, Light-headedness, dizziness, confusion, incoordination, drowsiness, or unconsciousness, irregular heartbeat with a strange sensation in the chest, heart thumping, apprehension, feeling of fainting, dizziness or weakness.

In high concentrations may cause asphyxiation. Symptoms may include loss of mobility/consciousness. Victim may not be aware of asphyxiation.

### 4.3. Indication of any immediate medical attention and special treatment needed

Treatment: None

## 5. FIRE-FIGHTING MEASURES

---

### 5.1. Extinguishing media

All known extinguishants can be used.

Extinguishing media which must not be used for safety reasons:

None in particular.

### 5.2. Special hazards arising from the substance or mixture

The product is not flammable in air, in a normal temperature and pressure conditions. Certain mixtures of the product with air, in certain conditions of pressure may be flammable. Avoid mixtures of the product with air, under pressure.

Certain mixtures of the product and chlorine may be flammable or reactive under certain conditions. Thermal



decomposition causes the emission of fumes very toxic and corrosive gases (hydrogen fluoride). Please observe section 10.

Containers may explode if heated

Do not inhale explosion and combustion gases.

### 5.3. Advice for fire-fighters

Use suitable breathing apparatus

Move undamaged containers from immediate hazard area if it can be done safely.

Cool containers/tank with water.

## 6. ACCIDENTAL RELEASE MEASURES

---

### 6.1. Personal precautions, protective equipment and emergency procedures

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Evacuate area.

Ensure adequate air ventilation.

Prevent from entering sewers, basements and workpits, or any place where its accumulation can be dangerous.

See protective measures under point 7 and 8.

### 6.2. Environmental precautions

Avoid discharge to atmosphere.

### 6.3. Methods and material for containment and cleaning up

Ventilate area.

### 6.4. Reference to other sections

See also section 8 and 13.

## 7. HANDLING AND STORAGE

---

### 7.1. Precautions for safe handling

Do not allow backfeed into the container.

Use only equipment suitable for the product and the operating pressure.

Avoid contact with skin and eyes, inhalation of vapours and mists.

Only experienced and properly instructed persons should handle compressed gases.

The substance must be handled in accordance with good industrial hygiene and safety procedures.

Close container valve after each use and when empty, even if still connected to equipment.

Never attempt to repair or modify container valves or safety relief devices.

Replace valve outlet caps or plugs and container caps where supplied as soon as container is disconnected from equipment.

Never use direct flame to raise the pressure of a container.

Do not remove or deface labels provided by the supplier for the identification of the cylinder contents.

Do not cut, drill, grind, weld or do similar operations on containers.

Please see also Section 8 for recommended protective equipment.

### 7.2. Conditions for safe storage, including any incompatibilities

Observe all regulations and local requirements regarding storage of containers.

Keep container in a well ventilated place.

Protect cylinders from physical damage; do not drag, roll, slide or drop.

Keep away from open flames, sparks and heat sources.

Keep container below 50 °C.

Containers should not be stored in conditions likely to encourage corrosion.

Incompatible materials:



See paragraph 10 below.  
Instructions as regards storage permises:  
Adequately ventilated.

7.3. Specific end use(s)  
If annexed, please make reference to the scenario

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

---

### 8.1. Control parameters

LELT (8 h TWA): 1000 (ml/m<sup>3</sup>)

LELT (8 h TWA): 4240 (mg/m<sup>3</sup>)

DNEL: Workers: 13936 mg/m<sup>3</sup> - Consumers: 2476 mg/m<sup>3</sup> - Exposure routes: Inhalation; Health effect: Chronic effects, Systemic toxicity.

PNEC: fresh water: 0.1 mg/l; marine water: 0.01 mg/l; water (Intermittent use/release): 1 mg/l; fresh water sediment: 0.75 mg/kg dry weight; water (sewage treatment plants): 73 mg/l.

### 8.2. Exposure controls

The product should be handled in a closed circuit..

Provide adequate general and local ventilation.

Make sure the exposure is well below the occupational exposure limits.

If the risk assessment indicates this is necessary, use the following protection

Eye protection:

Wear safety glasses with side shields

Protection for skin:

Protective clothing

Protection for hands:

Chemical resistant gloves and waterproof

Respiratory protection:

Wear self-contained breathing apparatus when entering area unless atmosphere is proved to be safe.

Thermal Hazards:

Contact with liquid may cause cold burns/frostbite.

Environmental exposure controls:

Refer to environment legislation

## 9. PHYSICAL AND CHEMICAL PROPERTIES

---

### 9.1. Information on basic physical and chemical properties

Appearance and colour:

Gas, Incolour

Odour:

Ethereal

Odour threshold:

Not available

pH:

Not applicable

Melting point / freezing point:

-108 ° C

Initial boiling point and boiling range:

-26.5 ° C

Solid/gas flammability:

Not applicable

Upper/lower flammability or explosive limits:

Not applicable

Vapour density:

3.6 (air=1)

Flash point:

Not applicable

Evaporation rate:

Not available

Vapour pressure:

5.7 bar (at 20°C)

Relative:

1.22 g/cm<sup>3</sup> (at 20°C)

Solubility in water:

Not available

Solubility (in other substances):

Alcohols, chlorinated solvents,  
polyethylene glycol



Partition coefficient n-octanol/water (POW):	1.06 (at 25°C)
Auto-ignition temperature:	Not applicable
Decomposition temperature:	Not available
Viscosity:	Not available
Explosive properties:	Not applicable
Oxidizing properties:	Not applicable

## 9.2. Other information

No data available

## 10. STABILITY AND REACTIVITY

---

### 10.1. Reactivity

The product is not flammable in air, in a normal temperature and pressure conditions. Certain mixtures of the product with air, under certain pressure conditions which may be flammable. Avoiding product mixtures with air under pressure.

Certain product mixtures and chlorine may be flammable or reactive under certain conditions. Thermal decomposition gas emissions very toxic and corrosive fumes (hydrogen fluoride)

### 10.2. Chemical stability

Stable in normal conditions

### 10.3. Possibility of hazardous reactions

Can react violently if in contact with alkali metals, alkaline earth metals.

### 10.4. Conditions to avoid

Avoid all possible sources of ignition (spark or flame). Do not cut, drill, grind or expose containers to heat.

### 10.5. Incompatible materials

Finely divided metals, magnesium and alloys containing more than 2% magnesium, powdered metal salts.

### 10.6. Hazardous decomposition products

Hydrogen fluoride by thermal decomposition and hydrolysis, carbon oxides, carbonyl fluoride, fluorocarbons.

## 11. TOXICOLOGICAL INFORMATION

---

### 11.1. Information on toxicological effects

Toxicological information of the substance:

Acute inhalation toxicity

LC50/4h - rat = 567000 ppm

Skin irritation: not known

Eye irritation: not known

Sensitisation: not known

Mutagenicity: not known

Carcinogenicity: not known

Toxicity to reproduction assessment: not known

STOT — single exposure: not known

STOT — repeated exposure: not known

Aspiration hazard: not known

## 12. ECOLOGICAL INFORMATION

---

### 12.1. Toxicity

Toxicity to fish: LC50/96h/rainbow trout (*Oncorhynchus mykiss*): 450 mg/l



# TAZZETTI

Toxicity to aquatic plants: EC50/72h/algae: >118 mg/l <sup>(1)</sup>

Toxicity to aquatic invertebrates: EC50/48h/daphnia magna: 980 mg/l

(1) : Information given is based on data obtained from similar substances.

## 12.2. Persistence and degradability

Not easily biodegradable

## 12.3. Bioaccumulative potential

Bioaccumulation is unlikely

## 12.4. Mobility in soil

No data available

## 12.5. Results of PBT and vPvB assessment

vPvB Substances: None - PBT Substances: None

## 12.6. Other adverse effects

Contains fluorinated greenhouse gases covered by the Kyoto protocol.

GWP: 1430

## 13. DISPOSAL CONSIDERATIONS

---

### 13.1. Waste treatment methods

Recover if possible. In so doing, comply with the local and national regulations currently in force.

Destruction should be on licensed premises equipped to absorb and neutralize acid gases and other toxic processing products.

Avoid release to the environment

Avoid discharge to atmosphere.

Recovering according to the supplier's instructions.

## 14. TRANSPORT INFORMATION

---

### 14.1. UN number

ADR/RID/IMDG/IATA - UN number: 3159

### 14.2. UN proper shipping name:

ADR/RID/IMDG - Shipping name: 1,1,1,2-TETRAFLUOROETHANE (REFRIGERANT GAS R134a)

IATA-Technical name: 1,1,1,2-TETRAFLUOROETHANE (REFRIGERANT GAS R134a)

### 14.3. Transport hazard class(es)

ADR/RID-Class: 2

ADR-Label: 2.2

RID-Label: 2.2 (+13)

ADR/RID - Hazard identification number: 20

Classification code: 2A

IATA/IMDG - Class: 2.2

### 14.4. Packing Group

ADR/IMDG - Packing Group: -

### 14.5. Environmental hazards: No

### 14.6. Special Precautions for User



ADR-Tunnel restriction code: C/E

IMDG stowage and segregation : Cat. A

IMDG Emergency schedules : F-C, S-V

Ensure there is adequate ventilation

Ensure vehicle driver is aware of the potential hazards of the load and knows what to do in the event of an accident or an emergency.

Compliance with applicable regulations.

Before transporting product containers :

- Ensure that containers are firmly secured.
- Ensure cylinder valve is closed and not leaking.
- Ensure valve outlet cap nut or plug (where provided) is correctly fitted.
- Ensure valve protection device (where provided) is correctly fitted.

Avoid transport on vehicles where the load space is not separated from the driver's compartment.

14.7. Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code: Not applicable

## 15. REGULATORY INFORMATION

---

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture  
Dir. 67/548/EEC (Classification, packaging and labelling of dangerous substances). Dir. 99/45/EEC (Classification, packaging and labelling of dangerous preparations). Dir. 98/24/EC (Risks related to chemical agents at work). Dir. 2000/39/EC (Occupational exposure limit values); Dir. 2006/8/CE. Regulation (CE) n. 1907/2006 (REACH), Regulation (CE) n. 1272/2008 (CLP), Regulation (CE) n. 790/2009 (1° ATP CLP), Regulation (EU) n. 453/2010 (Annex I).

Where applicable, refer to the following regulatory provisions :

Directive 2003/105/CE ('Activities linked to risks of serious accidents') and subsequent amendments.  
1999/13/EC (VOC directive)

15.2. Chemical Safety Assessment: No

## 16. OTHER INFORMATION

---

Revised safety data sheet in accordance with commission regulation (EU) No 453/2010

Ensure operators understand the flammability hazard.

Users of breathing apparatus must be trained.

Ensure operators understand the toxicity hazard.

This document was prepared by a competent person who has received appropriate training.

Main bibliographic sources:

ECHA: European chemical agency

ECDIN - Environmental Chemicals Data and Information Network - Joint Research Centre, Commission of the European Communities

SAX's DANGEROUS PROPERTIES OF INDUSTRIAL MATERIALS - Eight Edition - Van Nostrand Reinold

CCNL - Appendix 1

EIGA

The information contained herein is based on our state of knowledge at the above-specified date. It refers solely to the product indicated and constitutes no guarantee of particular quality.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

Classification in accordance with calculation methods of regulation (EC) 1272/2008 CLP / (EC) 1999/45 DPD.

The MSDS cancels and replaces any preceding release.

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

CAS: Chemical Abstracts Service (division of the American Chemical Society).



# TAZZETTI

CLP:	Classification, Labeling, Packaging..
DNEL:	Derived No Effect Level.
EINECS:	European Inventory of Existing Commercial Chemical Substances.
GHS:	Globally Harmonized System of Classification and Labeling of Chemicals.
IATA:	International Air Transport Association.
IATA-DGR:	Dangerous Goods Regulation by the "International Air Transport Association" (IATA).
ICAO:	International Civil Aviation Organization.
ICAO-TI:	Technical Instructions by the "International Civil Aviation Organization" (ICAO).
IMDG:	International Maritime Code for Dangerous Goods.
LC50:	Lethal concentration, for 50 percent of test population.
LD50:	Lethal dose, for 50 percent of test population.
LTE:	Long-term exposure.
PNEC:	Predicted No Effect Concentration.
RID:	Regulation Concerning the International Transport of Dangerous Goods by Rail.
STE:	Short-term exposure.
STEL:	Short Term Exposure limit.
STOT:	Specific Target Organ Toxicity.
TLV:	Threshold Limiting Value.
TWATLV:	Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).